

HUNTER PT150 1/4 (SMA-F)

Flexible full $1/4 \lambda$ TITANIUM alloy portable whip antenna with SMA-F connector

Flexible full $1/4 \lambda$ TITANIUM alloy portable whip antenna with integrated SMA-F connector.

- TITANIUM ALLOY RADIATING ELEMENT

ELECTRICAL SPECIFICATIONS

| | |
|------------------|-------------------|
| Frequency | 138-164 MHz (PMR) |
| Bandwidth | 26 MHz |
| Impedance | 50 ohm |
| Vswr | < 2.0 @ f.res. |
| Polarisation | Vertical |
| Gain | 0 dBd, 2.1 dBi |
| Max. Input Power | 50 W |



MECHANICAL SPECIFICATIONS

| | |
|-----------------------|-----------------------------------|
| Color | Black |
| Height | Approx. 460 mm |
| Weight | 20 g |
| Mounting Place | On handheld transceivers |
| Materials | POM, PE, Titanium alloy and brass |
| Operating Temperature | -40C to +70C |
| Connector | SMA female connector |

ORDERING INFORMATION

| | |
|-----|--|
| P/N | 14630 (Antenna whip only) |
| P/N | 14630IP (Antenna whip only - Bulk packing) |

PACKAGING INFORMATION

| | |
|------|-----------------|
| Type | Polybag or bulk |
|------|-----------------|

