



## Datasheet

2 / 2

## MECHANICAL SPECIFICATIONS

Color	Black
Dimension	Two units: 482.6 x 89.0 x 300 mm (W x H x L)
Weight	Single isolator: 9.5 kg Dual isolator: 10.1 kg
Connector	Type N-female
Serial no.	On product label
Operating temperature	-20° to +60°C

## ORDERING INFORMATION

55432-113	HCMR450-3S-L-5-150 400-440 MHZ 3CH x 100 W Single Isolator + DUPT-5
55434-123	HCMR450-3S-L-10-150 400-440 MHZ 3CH x 100 W Single Isolator + DUPT-10
55432-133	HCMR450-3S-H-5-150 440-475 MHZ 3CH x 100 W Single Isolator + DUPT-5
55434-143	HCMR450-3S-H-10-150 440-475 MHZ 3CH x 100 W Single Isolator + DUPT-10
55432-153	HCMR450-3D-L-5-150 400-440 MHZ 3CH x 100 W Dual Isolator + DUPT-5
55434-163	HCMR450-3D-L-10-150 400-440 MHZ 3CH x 100 W Dual Isolator + DUPT-10
55432-173	HCMR450-3D-H-5-150 440-475 MHZ 3CH x 100 W Dual Isolator + DUPT-5
55434-183	HCMR450-3D-H-10-150 440-475 MHZ 3CH x 100 W Dual Isolator + DUPT-10
Note	Power cable not included