

# CA02-0727035M

## Low Profile Cellular Antenna

High quality low profile Cellular antenna for through hole mounting.

- For roof mounting
- Low profile design
- Non-corrosive



## ELECTRICAL SPECIFICATIONS

Frequency	790 - 960 MHz, 1710 - 2690 MHz
Bandwidth	See "FREQUENCY"
VSWR	≤ 1.8:1
Impedance	50 Ohm
Gain	1 dBd, 3.15 dBi
Polarisation	Vertical
Max. Input Power	10 W

## MECHANICAL SPECIFICATIONS

Color	Black
Weight	110 g
Size	Ø 80 x 45 mm
Mounting	Bolt-on
Mounting Hole	Ø 17 mm
Mounting Place	On vertical or horizontal surfaces (conductive or non-conductive). E.g. car roofs, metering cabinets and brackets. (TBC)
Materials	PC, aluminum, brass, copper, PCB, PE (TBC)
Operating Temperature	-30 to +80° C
Cable	See "ORDERING INFORMATION"
Connector	See "ORDERING INFORMATION"
Serial No.	On product label

## ORDERING INFORMATION

CA02-0727035M/2.5	2.5 m RG174, SMA-male - In Polybag
CA02-0727035M/4	4.0 m CLF200, FME-female - In Polybag
CA02-0727035M/5	5.0 m CLF200, FME-female - In Polybag
CA02-0727035M/5-SMAM	5.0 m CLF200, SMA-male - In Polybag
CA02-0727035M/8	8.0 m CLF200, FME-female - In Polybag