Datasheet

DUPT-708

8-Cavity 150 Watts UHF 400 MHz Duplex Filter

- Wide bandwidth for multichannel operation
- For use in repeaters and full duplex radios.
- Steel chassis with aluminium extruded cavities.
- High Q resonators.
- Option for Rack Mount.

ELECTRICAL SPECIFICATIONS





Туре	UHF - 8 Cavity High Power Duplex Filter
Frequency	375 512 MHz (Please specify frequency for factory tuning)
Spacing	5-8 MHz 8-13 MHz
Insertion loss	≤ 1.5 dB
Isolation - Multi Channel	5-8 MHz: ≥ 75 dB @ BW ≤ 2.0 MHz 8-13 MHz: ≥ 75 dB @ BW ≤ 5.0 MHz
VSWR	≤ 1:1.5
Impedance	50 Ohm
Maximum Input Power	150 Watts
Frequency Stability	9 ppm/°C (approx.)

MECHANICAL SPECIFICATIONS

Color	Black Grey (RAL7021)
Dimension	410 x 240 x 55 mm
Weight	3.3 kg
Operating Temperature	-30°C to +60°C
Connector	Type N-female (other optional)
Serial no.	On product label

SCAN ANTENNA A/S | LITERBUEN 15 | 2740 SKOVLUNDE | DENMARK | +45 +454333 1620 Disclaimer: Here you find all products for a complete antenna system. One-stop supplier with focus on high quality products produced in EU. No matter which type of antenna you are searching for, you will find it here. Every effort has been made to ensure the accuracy of the information in this product sheet. Scan Antenna reserves the right to introduce changes to this information without notice. All rights reserved.

Scan-Antenna®

Datasheet

ORDERING INFORMATION

DUPT-708

375 - 512 Please specify frequency for factory tuning

SCAN ANTENNA A/S | LITERBUEN 15 | 2740 SKOVLUNDE | DENMARK | +45 +454333 1620 Disclaimer: Here you find all products for a complete antenna system. One-stop supplier with focus on high quality products produced in EU. No matter which type of antenna you are searching for, you will find it here. Every effort has been made to ensure the accuracy of the information in this product sheet. Scan Antenna reserves the right to introduce changes to this information without notice. All rights reserved.