Datasheet

# GPS-70G/804

## UHF/GPS - Combi magnitic Multiband mobile antenna with 3 dBd Gain Whip

The GPS-70G/804 is a mobile antenna with a UHF gain whip and magnetic base for roof mounting. Combining an integrated GPS antenna and a 3dB gain UHF whip, specifically 380-500 MHz.

With a meticulously constructed base made of PA, it is durable and strong.

The whip is made of stainless steel, black chromed to withstand the harshest conditions.

#### **ELECTRICAL SPECIFICATIONS**

Туре	UHF whip antenna (5/8 λ) GPS Magnetic Base Kit
Frequency	UHF: 380-500 MHz GPS: 1575.42 MHz
Bandwidth	20 MHz (UHF)
V.S.W.R	≤ 1.5:1
Impedance	50 Ohm
Polarisation	Linear (UHF), Right Hand Circular (RHC) (GPS)
Gain	3 dBd, 5.15 dBi (UHF)
LNA Gain	25 dB
Satellite System	GPS and Galileo
Noise Figure	Max 2.1 dB
Supply Voltage	2.7 - 5.0 VDC
Current Consumption, Average	12 mA @ 2.7 VDC 26 mA @ 5 VDC
Max. Input Power	50 W (UHF)



Printed: 4/21/2025

Datasheet

## **MECHANICAL SPECIFICATIONS**

Color	Black
Dimensions	Ø: 95 mm Whip length: approx. 580 mm
Weight	400 g
Mounting	Magnetic On horizontal surface (Vehicle roof etc.)
Mounting Instructions	Antenna Whip must be cut to specified frequency. See cutting diagram - TBA
Materials	PA, PCB, Black anodized steel
Operating Temperature	-30 to +80°C
Connector	BNC-male (UHF) SMA-male (GPS)
Cable	5.0 m RG-58 (UHF) 5.0 m RG-174 (GPS)
Ingress Protection	IP65 (When mounted)
Serial No.	On product label

### ORDERING INFORMATION

Base (BA 604) and write (Well-704)	GPS-70G/804	Base (BA-804) and Whip (WCK-70G)
------------------------------------	-------------	----------------------------------

#### PACKAGING INFORMATION

Туре	In Bag