Datasheet

1/2

G900+1800 0 dB POM (M5)

Dual-band rigid antenna whip

Rigid dual-band antenna whip especially made for use with "G"-type mounts (bases) on vehicle roof etc.

ELECTRICAL SPECIFICATIONS

Frequency	890 - 960 MHz, 1710 - 1880 MHz (GSM900/1800)
Bandwidth	See "FREQUENCY"
Impedance	50 ohm
Vswr	< 1.5
Polarisation	Vertical
Gain	0 dBd, 2.1 dBi
Max. Input Power	GSM900: 30 W, GSM1800: 10 W



MECHANICAL SPECIFICATIONS

Color	Black
Height	43 mm
Weight	7 g
Mounting	On "G"-type mounts
Mounting Place	Vehicle roof
Materials	Copper, POM and brass
Operating Temperature	-40C to +70C
Connector	M5 threaded stud

ORDERING INFORMATION

P/N

G12070POM (Bulk packing)


SCAN ANTENNA A/S | LITERBUEN 15 | 2740 SKOVLUNDE | DENMARK | +45 +454333 1620

Disclaimer: Here you find all products for a complete antenna system. One-stop supplier with focus on high quality products produced in EU. No matter which type of antenna you are searching for, you will find it here. Every effort has been made to ensure the accuracy of the information in this product sheet. Scan Antenna reserves the right to introduce changes to this information without notice. All rights reserved.

Scan-Antenna®

Datasheet

PACKAGING INFORMATION



SCAN ANTENNA A/S | LITERBUEN 15 | 2740 SKOVLUNDE | DENMARK | +45 +454333 1620 Disclaimer: Here you find all products for a complete antenna system. One-stop supplier with focus on high quality products produced in EU. No matter which type of antenna you are searching for, you will find it here. Every effort has been made to ensure the accuracy of the information in this product sheet. Scan Antenna reserves the right to introduce changes to this information without notice. All rights reserved.