

Datasheet

1 / 2

E65-75DKF 0 dB (M6)

Mobile reduced $1/4 \lambda$ spring loaded factory tuned antenna whip

Flexible spring loaded factory tuned antenna whip especially made for use with SX-Mount and Multimag on vehicle roof

- FACTORY TUNED

ELECTRICAL SPECIFICATIONS

Frequency	65 - 75 MHz (4M-BAND)
Bandwidth	10 MHz
Impedance	50 ohm
Vswr	< 2.0
Polarisation	Vertical
Gain	0 dBd, 2.1 dBi
Max. Input Power	100 W



MECHANICAL SPECIFICATIONS

Color	Black
Height	Approx. 540 mm
Weight	100 g
Mounting	On "E"-type mounts
Mounting Place	On vehicle roof
Materials	Stainless steel, glass-fibre, copper, PE and brass
Operating Temperature	-40C to +70C
Connector	M6 Internal thread

ORDERING INFORMATION

P/N	E12300
P/N	E12300IP (Bulk packing)

PACKAGING INFORMATION

Type	Polybag or bulk
------	-----------------



The image shows a technical drawing of a long, thin antenna with a coiled section at the end. A dimension line above the antenna indicates a total length of 540. A smaller dimension line to the right of the coiled section indicates a diameter or width of 15.75.